



L.H.R.B. R.H.R.B.
 1095 & 2095
 JACKSON CORP.
 LOS ANGELES, CA. 90023
 REV. "C" TEMPLATE 10-484

35 11/16 FROM THIS
 LINE TO FLOOR

FOR CYL. WITH 1/4 SPACING
 1 5/32 (REF. INST. INSTR.)
 DRILL 5/8 DIA.
 CENTERLINE OF
 PAD LOCATION
 OUTSIDE EDGE OF
 DOOR JAMB
 ACTIVE STILE

FOR CYL. WITH 3/8 SPACING
 DRILL .203 DIA.
 TAP 1/4-20 (2B)
 THREADS
 2 PLACES
 INST. INSTR.)
 1 5/32 (REF. INST. INSTR.)
 TOP
 LOCK STILE PAD
 DRILL 7/32 DIA.
 (SCREW HD. MUST BE
 FLUSH) 2 PLACES
 FOR CYLINDER ONLY

L.H.R.B. R.H.R.B.
 1095 & 2095
 JACKSON CORP.
 LOS ANGELES, CA. 90023
 REV. "C" TEMPLATE 10-484

35 11/16 FROM THIS
 LINE TO FLOOR

FOR CYL. WITH 1/4 SPACING
 1 5/32 (REF. INST. INSTR.)
 DRILL 5/8 DIA.
 CENTERLINE OF
 PAD LOCATION
 OUTSIDE EDGE OF
 DOOR JAMB
 ACTIVE STILE

FOR CYL. WITH 3/8 SPACING
 DRILL .203 DIA.
 TAP 1/4-20 (2B)
 THREADS
 2 PLACES
 INST. INSTR.)
 1 5/32 (REF. INST. INSTR.)
 TOP
 LOCK STILE PAD
 DRILL 7/32 DIA.
 (SCREW HD. MUST BE
 FLUSH) 2 PLACES
 FOR CYLINDER ONLY