



Price Page

**DETEX**

Vendor Site

## *ECL 230D* – Exit Control

### *Features:*

- Single point deadbolt locking device, 1” throw
- Unauthorized pressing of exit bar emits high decibel, 100db alarm
- Inside key control allows alarm bypass
- Accepts rim cylinder
- UL listed panic hardware
- 9 volt standard battery included
- Required Cylinder: Rim (not included)



### **Stocked Product**

- 230D

## *V40EB* – Exit Control

### *Features:*

- 100db alarm
- Powered by 9 volt battery included
- Low battery alert
- Red flashing LED alert when not armed
- Inside key control allows alarm bypass
- Accepts 1-1/8” mortise cylinder
- Latch bolt monitoring standard
- Required Cylinder: Mortise (not included)

### *Code Compliance:*

- Grade 1 UL listed panic
- Fire exit hardware
- UL listed for 3 hours
- UBC97 standard 7-2
- Exceeds ADA, CA title 19 ANSI / BHMA requirements



### **Stocked Product**

- V40EB for 36” door
- V40EBL for 48” door

## *EAX-500*

### *Features:*

- Lowcost, self contained door alarm with piezo horn
- Surface door mount only
- Patented plastic template allows for fool proof alignment of internal magnetic door contact
- Temper resistant housing
- Taper cover allows installation on 2” minimum stile doors
- Inside key control requires 1-1/8” mortise cylinder with standard Yale cam (supplied less cylinder)
- For outside key control (optional) use RIM cylinder (not supplied)

### **Stocked Product**

- EAX500

**EAX-500 - Is designed for applications that require an alarmed exit device on secured doors. Replaces old model EA-500**





**ABS-AMERICAN BUILDING SUPPLY, INC.**